

- Powered by ATI's next generation FireGL™ graphics processor unit with Avivo™ Technology
- Scalable ultra-threaded architecture with 8 Parallel Geometry Engines and 16 Pixel Shader Processors
- Full Shader Model 3.0 support for vertex and pixel shaders
- 512MB GDDR3 graphics memory with 512-bit ring bus memory controller
- High Dynamic Range (HDR) rendering with 8-bit, 10-bit & 16-bit per RGB color component support
- High fidelity display engine capable of producing over one trillion colors
- Two Dual Link outputs each capable of ultra-high resolutions up to 3840 x 2400
- Optimized and certified for CAD and DCC applications
- Direct access to ATI's dedicated workstation technical support team



ATI FireGL V7300 with



Industry Leading Ultra High-End Workstation Graphics Performance

Introducing the ATI FireGL V7300 with Avivo™ Technology - ultra high-end graphics acceleration for the most complicated 3D models, the largest data sets, and highest definition textures. The FireGL V7300 delivers industry leading features and performance for the most demanding workstation users running OpenGL and DirectX based applications.

Next Generation Workstation Graphics - Power for Today and Tomorrow

Featuring full Shader Model 3.0 support and a scalable ultra-threaded architecture with true 128-bit floating point precision, 8 parallel geometry engines, 16 pixel shader processors, and an ultra efficient 512-bit ring bus memory controller, ATI FireGL V7300 provides the graphics horsepower for today's professional applications and tomorrow's technology innovations. It's no wonder that animators, engineers and medical professionals are relying on next generation ATI FireGL workstation accelerators with Avivo Technology for better performance, higher image quality and superior value.

Unprecedented Visual Fidelity with ATI Avivo Technology

Designed with a 10-bit display pipeline and High Dynamic Range (HDR) 64-bit per pixel display capability, ATI FireGL workstation graphics accelerators with Avivo Technology can produce over one trillion colors for the most vibrant visual fidelity. Two Dual Link outputs each capable of driving ultra-high resolution cinema/widescreen monitors enables the FireGL V7300 to produce a massive multi-monitor display for greater productivity.

World Class Performance, Reliability, and Support

ATI FireGL workstation graphics accelerators are thoroughly tested and certified with all major Computer Aided Design (CAD) and Digital Content Creation (DCC) applications to ensure optimized performance and compatibility. FireGL unified drivers reduce total cost of ownership by simplifying system administration and maintenance. ATI offers direct customer access to a dedicated workstation technical support team.

FIREGL V7300 PRODUCT OVERVIEW

Overview

- Powered by advanced ATI FireGL Graphic Processor Unit (GPU) with Avivo™ Technology
- Scalable ultra-threaded architecture with fast dynamic branching and high performance parallel processing
- 8 parallel geometry engines and 16 pixel shader processors
- Full Shader Model 3.0 support
- 512MB GDDR3 graphics memory with 512-bit ring-bus memory controller
- 128-bit full floating point precision
- Native high bandwidth PCI Express x16 lane support

ATI Avivo™ Technology

- True 64-bit per pixel floating point High Dynamic Range (HDR) rendering support capable of over one trillion colors
- Full 10-bit precision display pipeline
- Advanced support for 8-bit, 10-bit, and 16-bit per RGB color component

System Requirements

- PCI Express® based workstation with available x16 lane graphics slot
- Connection to the system power supply (adapter included)
- 450-Watt power supply or greater (assumes fully loaded system)
- 512MB of system memory
- Installation software requires CD-ROM drive

Display Capabilities

- Dual DVI-I outputs support any combination of digital and analog displays
- Independent multi-monitor resolution and refresh rate selection
- Two Dual Link outputs ideal for driving two 30-inch cinema / widescreen (2560 x 1600) displays
- Individual Dual Link output capable of ultra-high resolutions up to 9 Megapixels (3840 x 2400)
- Stereoscopic 3D output connector with quad buffer support
- Dual VGA analog support ¹
- HD Component Video (YPrPb) output ²
- Genlock/Framelock ready ³

ATI Warranty and Support

- Three year limited product repair/replacement warranty
- Direct toll free phone and email access to dedicated workstation technical support team ⁴
- Advanced parts replacement option

API and OS Support

- OpenGL® 2.0 with OpenGL Shading Language
- Microsoft® DirectX® 9.0 with DX9 HLSL
- Windows® XP, Windows XP64 and Windows 2000
- Linux® 32 and Linux 64 ⁵

WORKSTATION MARKETS AND CERTIFICATIONS

Computer Aided Design

- Computer Aided Design (CAD)
- Architecture / Engineering / Construction (AEC)
- Medical Imaging
- Computational Fluid Dynamics
- Visual Simulation
- GIS / Mapping
- Oil & Gas

Certifications

- ABAQUS®
- Altair® Engineering Hyperworks®
- ANSYS Workbench™
- Autodesk® AutoCAD®, Inventor®, VIZ and Architectural Desktop
- Autodesk® StudioTools™
- Bentley MicroStation®
- ColCreate® OneSpace Designer Modeling
- Dassault Systemes CATIA®, ENOVIA® and SolidWorks®
- DELCAM™ PowerSHAPE™
- ESRI ArcGIS™
- ICEM® Surf
- MSC Software® MSC.Patran® and MSC.Nastran™
- Nemetschek Allplan
- PTC® Pro/CONCEPT™ and Pro/ENGINEER® Wildfire™
- Schlumberger Petrel
- UGS I-deas® NX, UGS NX, Solid Edge™ and Teamcenter Visualization

Digital Content Creation

- Game Development
- Cinematic Visual Effects
- Broadcast and Film Animation
- Virtual Set Design
- Compositing
- Digital Editing and Publishing

Certifications

- Adobe® After Effects®
- Adobe® Audition®
- Adobe® Encore™ DVD
- Adobe® Premiere® Pro
- Adobe® Photoshop® CS
- Autodesk® Maya®
- Autodesk® MotionBuilder
- Autodesk® 3ds Max®
- Autodesk® Combustion®
- Avid SOFTIMAGE® I XSI® and Avid Xpress Pro
- Maxon Cinema 4D
- Maxon BodyPaint 3D
- NewTek LightWave 3D®
- SensAble Technologies ClayTools™
- SensAble Technologies FreeForm® Concept™
- SensAble Technologies FreeForm® Modeling Plus™
- Side Effects Software™ Houdini™

ATI FireGL™ Workstation with Avivo Technology Graphics Accelerators

	Memory			Graphics Processing Unit						Avivo™ Technology			Display Capabilities				
	Memory Configuration	Memory Controller Interface	Memory Bandwidth (GB per second)	Ultra Threaded Architecture	Parallel Geometry Engines	Vertices per second	Pixel Shader Processors	Pixel Operations per second	Shader Model 3.0 Support	Full 10-bit Display Pipeline	64-bit per pixel HDR Rendering Support	Per Pixel Color Component Output	Display Output Connectors ¹	Dual Link Outputs	Stereoscopic 3D Output	HD Component Video Output ²	Genlock/Framelock Ready ³
FireGL V3100	128MB	128-bit	6.4		2	200M	4	1.6G				8-bit	VGA & DVI-I				
FireGL V5000	128MB	128-bit	13.8		6	638M	8	3.4G				8-bit	2 DVI-I	1	✓		
FireGL V5100	128MB	256-bit	22.4		6	675M	12	5.4G				8-bit	2 DVI-I		✓		
FireGL V7100	256MB	256-bit	30.4		6	750M	16	8.0G				8-bit	2 DVI-I	1	✓		
FireGL V7300	512MB	512-bit ring bus	41.6	✓	8	1200M	16	9.6G	✓	✓	✓	8, 10, 16-bit	2 DVI-I	2	✓	✓	✓
FireGL V7350	1GB	512-bit ring bus	41.6	✓	8	1200M	16	9.6G	✓	✓	✓	8, 10, 16-bit	2 DVI-I	2	✓	✓	✓

For additional information, visit FireGL.com

¹ VGA output supported through DVI-I to VGA adapters included with product

² HD Component Video (YPrPb) output adapter included with product

³ Genlock/Framelock support through advanced I/O daughter card available 2Ho6

⁴ Toll free hotline available in North America

⁵ Linux drivers can be downloaded from ati.com/FireGL