Hardware Notes - Pro/ENGINEER Wildfire 2.0 (including Structural and Thermal Option Wildfire 2.0)

Last updated: October 4, 2004

- Platform Support
- System Requirements
- Language Support
- Graphics Information
- Certified and Supported Graphics Cards
- Supported Peripherals and Accessories

Platform Suppo	ort				
Partner	Platform	Operating System levels	CPU	C Compiler (see note a below)	Fortran Compiler (see note a below)
Hewlett-Packard	HP-UX	11iV1 (64-bit only) 11 (64-bit only) Quality Pack Bundle March 2002	PA8000 or later	ANSI C++ (for Custom Loads) HP C 11.00.00	HP FORTRAN VB10.20.10
	Linux	Red Hat 7.3	Intel Pentium/Xeon	N/A	N/A
Microsoft Dell Fujitsu-Siemens Hewlett-Packard	Windows XP Professional Edition; Windows XP Home Edition	Base OS, Service Pack 1 and 2	Intel Pentium/Xeon family AMD Opteron family	MS Visual C++ V6.0	Compaq (DEC) Visual Fortran 6.0
- IBM - NEC	Windows 2000	Base OS, Service Pack 1, 2, 3 and 4	Intel Pentium/Xeon family		
SGI	IRIX64	6.5.18	Mips R8000 or later	C V7.3.1.3+	FORTRAN V7.2+
Sun	Solaris	8 and 9 (64-bit only)	UltraSPARC II or later	C 6.1	FORTRAN 5.0

NOTES

^aC Compiler is required only for the Structural and Thermal Option Wildfire 2.0. Fortran compiler is only required if you are running Fortran custom loads with the Structural and Thermal Option Wildfire 2.0

System Requirements							
·		Windows (XP (32-bit only) and 2000)		UNIX and Linux			
		Minimum	Recommended	Minimum	Recommended		
Main Memory		256 MB	512 MB or higher	256 MB	512 MB or higher		
Available Disk	Pro/ENGINEER and Conferencing	900 MB	900 MB or higher	1.2 GB	1.2 GB or higher		
Space	Pro/ENGINEER and Conferencing with Structural and Thermal Option Wildfire 2.0	1.2 GB	1.2 GB or higher	1.6 GB or higher	1.6 GB or higher		
Swap Space	Swap Space		1024 MB or higher	500 MB	1024 MB or higher		
CPU speed		500 MHz	1 GHz or higher	See above table for individual vendor proce support			
Internal Browser	Internal Browser Support		Microsoft Internet Explorer 6.0 SP1 or later		Browser is embedded in Pro/ENGINEER on the UNIX platform		
		Mozilla 1.0					
Monitor		1024 x 768 (or higher) resolution support with 24-bit or greater color		1024 x 768 (or higher) resolution support with 24-bit or greater color			
Network		Microsoft TCP/IP		TCP/IP			
		Ethernet Network Adapter		Ethernet Network Adapter			
Mouse		Microsoft-approved 3-button mouse		3-button mouse			
File systems		NTFS		All vendor-supported file systems.			
Misc.		CD-ROM or DVD drive		CD ROM or DVD drive			

Language Suppor	t		
Supported Language	Date Certified	Release Datecode	Comments
English	7-Nov-2003	2003400 and higher	
Chinese Simplified	19-Apr-2004	F000 and higher	Not yet available on Linux platform. Not supported by Structural and Thermal Option Wildfire 2.0.
Chinese Traditional	19-Apr-2004	F000 and higher	Not yet available on Linux platform Not supported by Structural and Thermal Option Wildfire 2.0.
French	19-Apr-2004	F000 and higher	Not yet available on Linux platform.
German	19-Apr-2004	F000 and higher	
Italian	19-Apr-2004	F000 and higher	Not yet available on Linux platform Not supported by Structural and Thermal Option Wildfire 2.0.
Korean	19-Apr-2004	F000 and higher	Not yet available on Linux platform Not supported by Structural and Thermal Option Wildfire 2.0.
Japanese	19-Apr-2004	F000 and higher	Not yet available on Linux platform.
Spanish	19-Apr-2004	F000 and higher	Not yet available on Linux platform Not supported by Structural and Thermal Option Wildfire 2.0.
NOTES			

Graphics Information

For 3D-hardware acceleration, an OpenGL graphics card must be used that has been tested in a PTC-certified configuration. To ensure the compatibility of a graphics driver with Pro/ENGINEER and Structural and Thermal Option Wildfire 2.0, a PTC-certified hardware configuration is recommended.

Dual Monitor Support

Limited dual monitor support is provided in Pro/ENGINEER Wildfire 2.0 on the Windows platform. PTC has successfully performed limited testing of some graphics card models from 3DLabs, ATI and NVIDIA that support dual monitor capabilities. If your graphics card is certified for Pro/ENGINEER Wildfire 2.0 and provides dual monitor support**, PTC expects that it will run in this mode without issue. PTC will provide limited support to resolve issues arising when running in dual monitor mode, however, the entire solution will not be submitted for formal certification as a complete configuration.

PTC has tested and officially supports the following graphics cards. This list is not meant to be a comprehensive listing of cards with dual monitor capabilities and it does not represent a shift from PTC's policy of certifying complete systems.

PTC's Support Policy.

Supported and tested graphics cards: ATI FireGL XL1 3DLabs Wildcat VP 990 Pro NVIDIA Quadro4 900XGL, 980XGL and FX 2000

Note: in the event that dual monitor mode fails, we advise use of Span mode as a workaround.

** Please consult with 3DLabs, ATI, NVIDIA, or the hardware platform partner to confirm the availability of this functionality with a given graphics card that has been certified with Pro/ENGINEER Wildfire 2.0.

Certified and Supported Graphics Cards

PTC provides Customer Support for all certified and/or supported graphics cards.

Supported	Graphics Cards			
Partner	Certified Graphics Cards	Certification Details	Supported Graphics Cards	Support Details
3Dlabs			Wildcat 4 7110	IBM
			Wildcat VP560	HP
			Wildcat VP760	HP
			Wildcat VP870	HP
			Wildcat VP880	HP

			Wildcat VP970	HP
			Wildcat VP990	HP
ATI	V3100	Dell, HP	MOBILITY FireGL T2	IBM
	Fire GL X1	HP	Fire GL X1	Dell, HP
	Fire GL4	HP	T2-128	IBM
	MOBILITY FireGL T2	HP		
	T2-128	HP		
Hewlett-	FireGL-UX	HP		
Packard	VISUALIZE – fx10	HP		
NVIDIA	Quadro FX 3000	Dell, HP	Quadro FX 3000	Dell, IBM
	Quadro FX 1100	HP, IBM	Quadro FX 2000	HP
	Quadro FX 1000	Dell, IBM		
	Quadro FX 700	Dell		
	Quadro FX 1300	Dell, HP	Quadro4 380 XGL	HP
	Quadro FX 3400	Dell	Quadro4 750 XGL	HP
	Quadro FX Go 1000	Dell	Quadro4 900 XGL	HP
	Quadro FX Go 700	Dell	Quadro4 980XGL	HP, IBM
SGI			Vpro V12	SGI
Sun			XVR-1200	Sun
			XVR-500	Sun
			XVR-600	Sun
			Elite3D	Sun

Supported Peripherals	and Accesso	ries			
	Windows (XP, 2000, NT 4.0)	Sun Solaris	HP-UX	SGI IRIX	Red Hat LINUX
3D Controllers (Pro/ENGINER information.	ER only) Please	refer to <u>http://ww</u>	w.3dconnexion.co	m/software/ for sp	ecific driver
SpaceTraveler	Certified	Certified	Certified	Certified	Certified
SpaceBall 5000	Certified	Certified	Certified	Certified	Certified

Plotters and Printers

Pro/ENGINEER supports HPGL, HPGL/2, PostScript, Calcomp, Gerber and Versatec standard plotting formats. In addition, Pro/ENGINEER supports the Microsoft Print Manager.

If you do not see your printer/plotter on the list below, please refer to the Introduction and Support Policy.

Emulation

Various manufacturers produce printers and plotters that may be compatible with or emulate a device that is supported by PTC. Please be aware that such devices are not tested by PTC and therefore, may not produce correct plotted output. If you are using a device which emulates a printer or plotter listed in the tables below, PTC Technical Support will attempt to provide support by using a similar certified device. Any support pertaining to compatibility with a supported plotter or the correctness of an emulation can only be made by the manufacturers of the device in question, and not by PTC.

The Microsoft Printer Manager creates an emulation of what appears on the screen and attempts to print this. Since this emulation is between the Print Manager driver and the printer/plotter driver, quality and results may vary. You may choose to try a certified PTC printer/plotter driver, which has been optimized for high quality printing.

Plotters					
HP designjet 1055CM+	Certified	Certified	Certified	Certified	Not Supported or Certified
HP designjet 800PS	Certified	Certified	Certified	Certified	Certified
HP designjet 5500PS	Certified	Certified	Certified	Certified	Certified
HP designjet copier cc800PS	Certified	Certified	Certified	Certified	Certified
Printers					
HP deskjet 1220cps	Certified	Certified	Certified	Certified	Not Supported or Certified
HP color inkjet cp1700ps	Certified	Certified	Certified	Certified	Not Supported or Certified

Certified Certified Certified Certified	HP business inkjet 2600dn	Certified	Certified	Certified	Certified	Not Supported or Certified
---	---------------------------	-----------	-----------	-----------	-----------	-------------------------------