

----- Flansch -----				
200	bis	1600	Weld neck flange C, DIN 2632	●
15	bis	500	Weld neck flange C, DIN 2633	●
----- Dichtung -----				
250	bis	1600	Flat ring gasket, 10, DIN EN 1514-1, IBC	●
100	bis	500	Flat ring gasket, 16, DIN EN 1514-1, IBC	●
15	bis	150	Flat ring gasket, 40, DIN EN 1514-1, IBC	●
----- Rohr -----				
8	bis	150	Pipe DIN 2448	
200	bis	2000	Pipe DIN 2458	
----- Reduzierstück -----				
250	bis	1200	Reducer, conc., DIN 2616-2	●
20	bis	200	Reducer, conc., DIN 2616-2	●
20	bis	200	Reducer, ecc., DIN 2616-1	●
250	bis	1000	Reducer, ecc., DIN 2616-1	●
----- Sieb -----				
80	bis	80	Strainer, Type Y, PN16	
----- Armatur -----				
10	bis	50	Ball Valve, Handlever, buttweld ends	●
200	bis	600	Butterfly Valve, PN 10, C	
40	bis	150	Butterfly Valve, PN 16, C	●
25	bis	100	Check valve, PN 16, C	●
50	bis	50	Flow measurement PN 10, C	●
100	bis	100	Safety Corner Valve, Spring loaded PN 16, B1	●
100	bis	100	Safety Corner Valve, Spring loaded PN 16, C_TEST	●
80	bis	150	Sight Glass, PN 16	●

Au

--

--

--

Iszug Rohrklasse