ZI 942/... Sealing Plugs

for heating / cooling lines in molds and dies

Available in


Inch-dimensions


Dia.	1/4	5/16	3/8
Dia.	7/16	9/16	11/16




Features

- Tried and true solution for the diverting of water, oil or air flow through intersecting circuits in molds and dies.
- Rust-free Seal Plugs are made with inner stainless steel core and outer brass sleeve.
- Easy to use assembly tool for installing Seal Plugs.
- Positioning Seal Plugs is fast and easy with scale tube and positive stop.
- Draw bar unscrews quickly after plugs have been set.
- Handy storage kit for all components.
- Multiple plugs installed in just minutes.










Table 1. Applicable mounting depths for the various plug sizes

dT	5-7/8	7-7/8	9-1/4	9-7/8	12-3/8	15-3/4	24-3/4	31-1/2
1/4	ZI 945/#1							
5/16		ZI 945/#1			ZI 947/#1			
3/8			ZI 945/#1			ZI 947/#1		
7/16				ZI 945/#2		ZI 947/#2		
9/16				ZI 945/#2			ZI 947/#2	
11/16				ZI 945/#2				ZI 947/#2

Table 2. Standard Values for Hole Tolerances and Pressures




Table 3. Hole Tolerances

Dia.	Standard Fits (Values are in thousandths of an inch)				
[inch]	H 5	Η 7	H 9	H 11	H 13
1/4	. 0.1	. 50	. 1.40	.0.54	. 0. 00
5/16	+.24	+.59	+1.42	+3.54	+8.66
3/8	0	0	0	0	0
7/16	. 01	. 71	.1.60	. 4 00	. 10.62
9/16	+.31	+.71	+1.69	+4.33	+10.63
11/16	0	0	0	0	U

For further information please refer to the "HASCO-Specification Sheet for Allowances and Tolerances".

Important Information


HASCO Sealing Plugs are a tried and true solution for the diverting of water, oil or air flow through intersecting circuits in molds and dies. Accurate spacing and positive sealing is insured. For gun drilled holes, the extended mounting bar ZI 947/... should be used (see Table 1). Depending on the bore tolerance

(see Table 2), the mounted Sealing Plugs withstand pressure up to 680 psi (40 bar). The Sealing Plugs ZI 942/... should not be used in place of pipe plugs. For this purpose, only threaded plugs must be used. Please refer to Figure 1.

HASCO

Mounting Kit

The mounting kit ZI 945/.. contains an assortment of three sealing plug sizes, the assembly tool and matching mounting bars. These can easily be inserted into the assembly tool. When working with different Sealing Plug sizes the matching mounting bar must be used with the assembly tool. Two types of mounting kits are offered.




ZI 945/#1 Mounting Kit

Qty		d	I	#	Order No.
25	ZI 942/1/4	1/4	5-7/8	٦	
25	ZI 942/5/16	5/16	7-7/8	}1	ZI 945/#1
25	ZI 942/3/8	3/8	9-1/4	J	

ZI 947/#1/... Extended Mounting Kit

#	d	I	Order No.
1	5/16	12-3/8	ZI 947/#1/5/16x12-3/8
1	3/8	15-3/4	ZI 947/#1/3/8x15-3/4




ZI 945/#2 Mounting Kit

Qty		d	I	#	Order No.
25	ZI 942/7/16	7/16	9-7/8	٦	
20	ZI 942/9/16	9/16	9-7/8	2	ZI 945/#2
15	ZI 942/11/16	11/16	9-7/8	J	

ZI 947/#2/... Extended Mounting Kit

#	d	I	Order No.
2	7/16	15-3/4	ZI 947/#2/7/16x15-3/4
2	9/16	24-3/4	ZI 947/#2/9/16x24-3/4
2	11/16	31-1/2	ZI 947/#2/11/16x31-1/2

HASCO



Notes:

Please note: Metric dimensions of Sealing Plugs with diameters of 6, 8, 10, 12 and 16 mm for water line depth up to 31-1/2 (800 mm) are offered in the HASCO Metric Catalog. To distinguish them, the inch Sealing Plugs are black anodized and the metric Sealing Plugs have a metallic finish.

Please refer to our Operating Manual for further information.

Four HASCO AMERICA Locations to Service You Better:

HASCO-EAST 140 Vista Boulevard Arden NC 28704 Ph: (828) 650-2600 Fax: (828) 684-7960 HASCO-WEST 21200 Superior Street Chatsworth CA 91311 Ph: (818) 709-4891 Fax: (818) 407-5846 HASCO-CANADA 60 Ironside Crescent Units 6&7, Scarborough Ontario M1X 1G4 Ph: (416) 293-5044 Fax: (416) 293-5110 HASCO-MEXICO Manuel de Navarrete No.10 Cto. Poetas, Ciudad Satélite 53100 Naucalpan, Estado de México Ph: (52) 5572-7755 Fax: (52) 5393-8841

info.america@hasco.com · www.hasco.com