Copyright 2010 Siemens Product Lifecycle
Management Software Inc.
All Rights Reserved.

This software and related documentation are
proprietary to Siemens Product Lifecycle
Management Software Inc.

Siemens and the Siemens logo are registered
trademarks of Siemens AG. NX is a trademark or
registered trademark of Siemens Product
Lifecycle Management Software Inc. or its
subsidiaries in the United States and in other
countries. NASTRAN is a registered trademark
of the National Aeronautics and Space
Administration. All other trademarks,
registered trademarks or service marks belong
to their respective holders.

LIMITATIONS TO U.S. GOVERNMENT RIGHTS. UNPUBLISHED
- RIGHTS RESERVED UNDER THE COPYRIGHT LAWS OF THE
UNITED STATES. This computer software and related
computer software documentation have been
developed exclusively at private expense and are
provided subject to the following rights: If this
computer software and computer software
documentation qualify as "commercial items" (as
that term is defined in FAR 2.101), their use,
duplication or disclosure by the U.S. Government
is subject to the protections and restrictions as
set forth in the Siemens commercial license for
software and/or documentation, as prescribed in
FAR 12.212 and FAR 27.405(b)(2)(i) (for civilian
agencies) and in DFARS 227.7202-1(a) and DFARS
227.7202-3(a) (for the Department of Defense), or
any successor or similar regulation, as applicable
or as amended from time to time. If this computer
software and computer documentation do not qualify
as "commercial items", then they are "restricted
computer software" and are provided with "restric-
tive rights", and their use, duplication or dis-
closure by the U.S. Government is subject to the
protections and restrictions as set forth in FAR
27.404(b) and FAR 52-227-14 (for civilian agencies
), and DFARS 227.7203-5(c) and DFARS 252.227-7014
(for the Department of Defense), or any successor
or similar regulation, as applicable or as amended
from time to time. Siemens PLM Software Inc.
5400 Legacy Drive, Plano, Texas 75024-3199.

```
* * * * * * * * * * * * * * * * * * * * *
* * * * * * * * * * * * * * * * * * * * *
* *                                   * *
* *                                   * *
* *                                   * *
* *                                   * *
* *       N X   N a s t r a n         * *
* *                                   * *
* *         VERSION -   8.0           * *
* *                                   * *
* *          MAY 18, 2011             * *
* *                                   * *
```

```
                    kupplungversuch_sim1-solution_1
              * *                                  * *
              * *Intel64 Family 6 Model 23 Steppi * *
              * *                                  * *
              * *Intel(R) Core(TM)2 Quad CPU Q900 * *
              * *                                  * *
              * *            Windows 7             * *
              * *                                  * *
              * *       Compiled for X86-64        * *
              * *                                  * *
              * * * * * * * * * * * * * * * * * * * * *
              * * * * * * * * * * * * * * * * * * * * *
1

                      Welcome to NX Nastran
                      -------------------------


 This "news" information can be turned off by setting "news=no" in the runtime
 configuration (RC) file.  The "news" keyword can be set in the system RC file
 for global, or multi-user control, and in a local file for local control.
 Individual jobs can be controlled by setting news to yes or no on the command
 line.
1
FEBRUARY  21, 2013  NX NASTRAN  5/18/11   PAGE     1


0       N A S T R A N   F I L E   A N D   S Y S T E M   P A R A M E T E R
 E C H O
0




     NASTRAN BUFFSIZE=8193 $(C:/PROGRAM FILES/SIEMENS/NX
8.0/NXNASTRAN/CONF/NAST8.RCF
     NASTRAN DIAGA=128 DIAGB=0 $(C:/PROGRAM FILES/SIEMENS/NX
8.0/NXNASTRAN/CONF/NAST8
     NASTRAN SYSTEM(442)=1 $(COMMAND LINE[6])

     NASTRAN REAL=1069023232 $(PROGRAM DEFAULT)

     $*$$$
```

```
$*      NASTRAN LICENSE: DESKTOP BUNDLE

$*

$*                UNITS: MM (MILLI-NEWTON)

$*                      ... LENGTH : MM

$*                      ... TIME   : SEC

$*                      ... MASS   : KILOGRAM (KG)

$*                      ... TEMPERATURE : DEG CELSIUS

$*                      ... FORCE  : MILLI-NEWTON

$*                      ... THERMAL ENERGY : MN-MM (MICRO-JOULE)

$*

$* WICHTIGER HINWEIS:

$*     DIESER TITEL WURDE VON NX ERSTELLT, UND DIE |NDERUNG DIESER
INFORMATIONEN
$*     BEEINTR|CHTIG U. U. DIE NACHBEARBEITUNG VON ERGEBNISSEN IN NX.

$*

$*$$$
```

```
     ID,NASTRAN,KUPPLUNGVERSUCH_SIM1-SOLUTION_1

     SOL 601,106

 solution 601 with 106
     CEND

1
FEBRUARY  21, 2013  NX NASTRAN  5/18/11   PAGE     3


0

0                                        C A S E    C O N T R O L    E C H O

                 COMMAND

                 COUNT

                  1      $*

                  2      $*$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$

                  3      $*

                  4      $* CASE CONTROL

                  5      $*

                  6      $*$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$

                  7      $*

                  8      ECHO = NONE

                  9      BCSET = 100

                 10      TEMP(INIT) = 200

                 11      TSTEP = 100

                 12      OUTPUT

                 13      BCRESULTS(TRACTION,FORCE,PLOT) = ALL

                 14      DISPLACEMENT(PLOT,REAL) = ALL

                 15      NLSTRESS(PLOT) = ALL

                 16      SPCFORCES(PLOT,REAL) = ALL

                 17      STRESS(PLOT,REAL,VONMISES,CENTER) = ALL

                 18      $*  NX STEP: SUBCASE - NONLINEAR IMPLICIT

                 19      SUBCASE 1

                 20      LABEL = SUBCASE - NONLINEAR IMPLICIT

                 21      DLOAD = 301

                 22      SPC = 6
```

```
                 23      $*

                 24      $*$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$

                 25      $*

                 26      $* BULK DATA

                 27      $*

                 28      $*$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$$

                 29      $*

                 30      BEGIN BULK

0                            INPUT BULK DATA ENTRY COUNT =  101495
0                       TOTAL COUNT=    101456
1
FEBRUARY  21, 2013  NX NASTRAN  5/18/11   PAGE     4


0

0
0
0
```

M O D E L S U M M A R Y

```
                                  NUMBER OF GRID     POINTS   =    14022

                                  NUMBER OF CTETRA   ELEMENTS =    61989

 *** USER INFORMATION MESSAGE 4109 (OUTPX2)
     THE LABEL IS NXNADINA FOR FORTRAN UNIT 21
     (MAXIMUM SIZE OF FORTRAN RECORDS WRITTEN =        7 WORDS.)
     (NUMBER OF FORTRAN RECORDS WRITTEN =        8 RECORDS.)
     (TOTAL DATA WRITTEN FOR TAPE LABEL =       17 WORDS.)
 *** USER INFORMATION MESSAGE 4114 (OUTPX2)
     DATA BLOCK CASECC   WRITTEN ON FORTRAN UNIT 21, TRL =
                  101                 1                 0               600
             0                 0                 0
     (MAXIMUM POSSIBLE FORTRAN RECORD SIZE =    16386 WORDS.)
     (MAXIMUM SIZE OF FORTRAN RECORDS WRITTEN =      600 WORDS.)
     (NUMBER OF FORTRAN RECORDS WRITTEN =       19 RECORDS.)
     (TOTAL DATA WRITTEN FOR DATA BLOCK =      624 WORDS.)
 *** USER INFORMATION MESSAGE 4114 (OUTPX2)
     DATA BLOCK IBULK    WRITTEN ON FORTRAN UNIT 21, TRL =
                  102                 1                 0                 0
             0                 0                 0
     (MAXIMUM POSSIBLE FORTRAN RECORD SIZE =    16386 WORDS.)
     (MAXIMUM SIZE OF FORTRAN RECORDS WRITTEN =       20 WORDS.)
     (NUMBER OF FORTRAN RECORDS WRITTEN =   507289 RECORDS.)
     (TOTAL DATA WRITTEN FOR DATA BLOCK =  2434941 WORDS.)
1
FEBRUARY  21, 2013  NX NASTRAN  5/18/11   PAGE     5


0

0
```

```
 *** USER INFORMATION MESSAGE 4114 (OUTPX2)
     DATA BLOCK MPT      WRITTEN ON FORTRAN UNIT 21, TRL =
                  104             34816                 0                 0
            0                 0                 0
     (MAXIMUM POSSIBLE FORTRAN RECORD SIZE =    16386 WORDS.)
     (MAXIMUM SIZE OF FORTRAN RECORDS WRITTEN =       15 WORDS.)
     (NUMBER OF FORTRAN RECORDS WRITTEN =       29 RECORDS.)
     (TOTAL DATA WRITTEN FOR DATA BLOCK =       64 WORDS.)
 *** USER INFORMATION MESSAGE 4110 (OUTPX2)
                                 END-OF-DATA SIMULATION ON FORTRAN UNIT 21
                                 (MAXIMUM SIZE OF FORTRAN RECORDS WRITTEN =
1 WORDS.)
                                       (NUMBER OF FORTRAN RECORDS WRITTEN =
1 RECORDS.)
                                       (TOTAL DATA WRITTEN FOR EOF MARKER =
1 WORDS.)
 ^^^SOLUTION MONITOR FLAG =          1
 ^^^HICORE MEMORY =   26214404
 ^^^REAL MEMORY IN WORDS =  1069023232
 ^^^MEMORY PASSED TO ADINA IN MB           100
 ^^^OPTION FLAG GIVEN TO ADINA           1
 *** ISHELL PROGRAM 'NXNA' STARTED ***
 *** ADVANCED NONLINEAR ANALYSIS ***
 *** START SOL 601 ***
 *** TEMPORARY FILES tmpadvnlin.* WILL BE CREATED DURING ANALYSIS RUN ***
 *** PROCESS NASTRAN DATA ***
 *** ADNAST (04/06/11 16:53) ***
 *** Allocating 256 MB of memory ...


     *** Reading Nastran data ...


     ***WARNING: No element connection for node 1 directions 4, 5, 6
     ***WARNING: Similar warning suppressed for 13566 other nodes.
     ***WARNING: Nodal degrees of freedom without element
                 connection have been fixed for data input file.
     *** ADINA data input file tmpadvnlin.dat successfully created.

 *** EXECUTE SOLUTION ***
 PID=3280
 Checked out NX Nastran license feature nx_nas_advnlin_dsk.
 Initializing ... Stage 1
 Allocating 32.0 MB of memory ...


        ***************************************************************
        *                                                             *
        *    P R O G R A M   N X   N A S T R A N   S O L   6 0 1      *
        *                                                             *
        ***************************************************************


        COPYRIGHT  ADINA R&D,INC., 2004,2005,2006,2007,2008,2009,2010


        ADINA IS A REGISTERED TRADEMARK OF K.J. BATHE.


                         *** ADINA R&D INC. ***
        MAKES NO WARRANTY WHATSOEVER, EXPRESSED OR IMPLIED THAT
        THE PROGRAM AND ITS DOCUMENTATION ARE FREE FROM ERRORS
        AND DEFECTS. IN NO EVENT SHALL ADINA R&D BECOME LIABLE
        TO THE USER OR ANY PARTY FOR ANY LOSS, INCLUDING BUT NOT
        LIMITED TO, LOSS OF TIME, MONEY OR GOODWILL, WHICH MAY
        ARISE FROM THE USE OF THE PROGRAM AND ITS DOCUMENTATION.
```

```
      COMPUTER VERSION:   Windows 64-BIT VERSION


      NOTE: ELEMENT GROUP NUMBERS ARE EQUIVALENT TO
            ELEMENT PID NUMBERS

Initializing ... Stage 2
Initial ADINA memory allocation  -    32.0 mb  (or    4.0 mw)
Starting Solution Process ...


         ************************************************************
         *                                                          *
         *          THIS IS A NONLINEAR   STATIC SOLUTION           *
         *                                                          *
         ************************************************************

                     ***   MEMORY REALLOCATION   ***
  REQUESTED MEMORY FROM THE SYSTEM...=      32.0 mb    (       4.0 mw)

Re-allocating 36.6 MB of memory ...

*** W A R N I N G ***

CONTACT GROUP NUMBER=       100

SOME CONTACT NODES BELONG TO MORE THAN ONE CONTACTOR SURFACE.
THIS MAY RESULT IN OVER-CONSTRAINING (ESPECIALLY WITH FRICTION).
USE A COMPLIANCE FACTOR TO AVOID OVER-CONSTRAINING.

      1. Node=     13222 belongs to surface         1 and surface         7
      2. Node=     13168 belongs to surface         1 and surface         7
      3. Node=     13169 belongs to surface         1 and surface         7
      4. Node=     13201 belongs to surface         1 and surface         7
      5. Node=     13435 belongs to surface         1 and surface         7
      6. Node=     13196 belongs to surface         1 and surface         7
      7. Node=     13233 belongs to surface         1 and surface         7
      8. Node=     13234 belongs to surface         1 and surface         7
      9. Node=     13220 belongs to surface         1 and surface         7
     10. Node=     13438 belongs to surface         1 and surface         7
     ...
     41. A total of       31 similar messages suppressed for surface         1
     42. Node=      3915 belongs to surface         3 and surface         7
     43. Node=      3910 belongs to surface         3 and surface         7
     44. Node=      3681 belongs to surface         3 and surface         7
     45. Node=      4354 belongs to surface         3 and surface         7
     46. Node=      3678 belongs to surface         3 and surface         7
     47. Node=      3679 belongs to surface         3 and surface         7
     48. Node=      3680 belongs to surface         3 and surface         7
     49. Node=      3919 belongs to surface         3 and surface         7
     50. Node=      3920 belongs to surface         3 and surface         7
     51. Node=      4356 belongs to surface         3 and surface         7
     ...
     73. A total of       22 similar messages suppressed for surface         3

                     ***   MEMORY REALLOCATION   ***
  REQUESTED MEMORY FROM THE SYSTEM...=      64.0 mb    (       8.0 mw)

Re-allocating 68.7 MB of memory ...

                     ***   MEMORY REALLOCATION   ***
  REQUESTED MEMORY FROM THE SYSTEM...=      72.0 mb    (       9.0 mw)

Re-allocating 79.1 MB of memory ...

PROGRAM SOL601, build date: 04.11.2011    *** NO HEADING DEFINED ***
```

```
 S O L U T I O N   B Y   S P A R S E   S O L V E R


 TOTAL SYSTEM DATA

     TOTAL NUMBER OF EQUATIONS . . . . . . . . . .(NEQ)  =     53979

     NUMBER OF EQUATIONS EXCLUDING CONTACT . . . (NEQI)  =     40701

     NUMBER OF CONTACT EQUATIONS . . . . . . . . (NCEQ)  =     13278

     NUMBER OF NON-ZERO MATRIX TERMS. . . . . . . (NZC)  =   1023010

     MEMORY AVAILABLE FOR STORAGE (in megawords) . . . . =         9

     NUMBER OF PROCESSORS USED. . . . . . . . . (NPROC)  =         1

 Re-allocating 421.0 MB of memory ...


       M E M O R Y     R E Q U I R E M E N T   (in words)

  ALLOCATED MEMORY BY THE PROGRAM (MSTORE)              =            52630803
  ESTIMATED MEMORY FOR IN-CORE STORAGE .......(IOPTIM=3)=            52630703
  ESTIMATED MEMORY FOR K-MATRIX IN-CORE ONLY..(IOPTIM=2)=             9939575
  NOTE: WHEN SPARSE SOLVER IS USED - ADDITIONAL MEMORY
        IS REQUIRED - PLEASE SEE BELOW INFORMATION
        RELATED TO SPARSE SOLVERS.

  MAXIMUM REQUESTED (TEMPORARY) MEMORY (in words)...... =            52630703

     IN-CORE STORAGE FLAG . . . . . . . . . . . (IOPTIM)  =         3


                      ***   MEMORY REALLOCATION   ***
   REQUESTED MEMORY FROM THE SYSTEM...=     432.0 mb    (      54.0 mw)

 Re-allocating 437.5 MB of memory ...

 ******************************************************************************
 Allocated memory for storage of model data . . :     437.5 mb
 Memory used for storage of model data. . . . . :     437.5 mb

 ******************************************************************************

 Contact group        100 has       67 initially touching contactor nodes
                    *** WARNING NO. A3   ***
 Contact group     100 has     1395 initially penetrating contactor nodes
 Maximum penetration: 0.1098667E+02

 NOTE:
 Nodes can be initially in contact either by design or due to finite element
discretization or due to
 a modeling error. Therefore, please check the contact surface definitions
(especially in the case of
 a gross overlap). Also check the orientation of all contact surfaces
```

(especially the target surfaces).

```
 TIMING INFORMATION FOR THE SOLUTION OF EQUATIONS FOR THE FIRST STEP

 TIME AT ENTERING THE EQUATION SOLVER  . . =     13.18


 ***************************************************************************
 *                                                                         *
 *          <<<<< SPARSE SOLVER INFORMATION >>>>>                          *
 *                                                                         *
 * NUMBER OF NON-ZERO TERMS IN FACTORIZED MATRIX......=            19420831  *
 * MEMORY USED BY THE SOLVER (in words)...............=            20612184  *
 * TOTAL MEMORY USED BY THE PROGRAM (in words)........=            75296420  *
 *              << IN-CORE SOLUTION >>                                     *
 ***************************************************************************


 Memory used by the in-core sparse solver. . :     164.9 mb
 Total memory used by the program. . . . . . :     602.4 mb


 TIME AT THE END OF SOLUTION OF EQUATIONS  =     22.71


  STEP NUMBER =         1     ( TIME STEP = 0.20000E+00   SOLUTION TIME =
0.20000E+00 )
 DIAG ELEMENT (WITH MAX ABS VALUE) OF THE FACTORIZED MATRIX =    0.65174E+10
NODE =      9985     DOF = X-TRANSLATION
 DIAG ELEMENT (WITH MIN ABS VALUE) OF THE FACTORIZED MATRIX =    0.23726E+06
NODE =      9836     DOF = Y-TRANSLATION


 METHOD  STEP-NUMBER  SUBINCREMENT    TIME STEP    SOLUTION TIME   INITIAL
ENERGY
 *ATS*          1          1       0.200000E+00     0.200000E+00
0.473444E+05


 I N T E R M E D I A T E   P R I N T O U T   D U R I N G   E Q U I L I B R I U M
  I T E R A T I O N S


          OUT-OF-         NORM OF
CONVERGENCE RATIOS  CONVERGENCE RATIOS   OUT-OF-BALANCE LOAD
          BALANCE     OUT-OF-BALANCE        NORM OF INCREMENTAL         FOR
OUT-OF-BALANCE    FOR INCREMENTAL    VECTOR CALCULATION
          ENERGY      FORCE    MOMENT      DISP.      ROTN.    CFORCE
ENERGY     FORCE    DISP.     CFORCE      BETA      RATIO
                    NODE-DOF   NODE-DOF   NODE-DOF   NODE-DOF   CFNORM
     MOMENT   ROTN.                (ITERNS)
                   MAX VALUE  MAX VALUE  MAX VALUE  MAX VALUE

COMPARE WITH        COMPARE WITH
                                                                          ETOL
      RTOL     DTOL      RCTOL

1.00E-03 (NOT USED)(NOT USED) 5.00E-02

 ITE=  0  4.73E+04  8.00E+04   0.00E+00   6.44E+01   0.00E+00  4.63E+09
1.00E+00  1.00E+00  8.03E+00  4.63E+11
                     12347-Z        0-F    14006-X        0-F  0.00E+00
    0.00E+00  0.00E+00
                    3.10E+03   0.00E+00  -1.20E+00   0.00E+00
```

```
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1564E+00

 ITE=  1  1.34E+09  2.86E+09   0.00E+00   1.01E+02   0.00E+00  7.76E+08
2.83E+00  3.57E+04  1.00E+00  1.38E+00  1.00E+00  1.75E+05
                     10002-X        0-F    13613-Y        0-F  5.63E+08
    0.00E+00  0.00E+00               ( 1)
                    5.22E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1668E+00

 ITE=  2 -7.82E+08  2.70E+09   0.00E+00   6.48E+00   0.00E+00  1.18E+09
-1.65E+00  3.37E+04  6.43E-02  9.42E-01  1.00E+00 -3.12E-01
                     14006-X        0-F    13936-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                    5.64E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4462E-01

 ITE=  3 -7.17E+07  2.47E+09   0.00E+00   3.61E+00   0.00E+00  8.96E+08
-1.51E-01  3.09E+04  3.58E-02  7.14E-01  1.00E+00  1.13E+00
                     14006-X        0-F    14005-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                    5.45E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2372E-01

 ITE=  4 -2.92E+08  2.33E+09   0.00E+00   2.46E+00   0.00E+00  8.59E+08
-6.18E-01  2.92E+04  2.44E-02  6.08E-01  1.00E+00 -5.82E+00
                     14006-X        0-F    14004-X        0-F  1.41E+09
    0.00E+00  0.00E+00               ( 1)
                    5.12E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1810E-01

 ITE=  5  6.56E+08  2.34E+09   0.00E+00   2.38E+00   0.00E+00  6.80E+08
1.39E+00  2.93E+04  2.36E-02  4.40E-01  1.00E+00  3.22E-02
                     13930-X        0-F    13935-X        0-F  1.55E+09
    0.00E+00  0.00E+00               ( 1)
                    5.08E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2612E-01

 ITE=  6  5.11E+08  2.26E+09   0.00E+00   2.86E+00   0.00E+00  1.11E+09
1.08E+00  2.83E+04  2.84E-02  6.35E-01  1.00E+00  5.78E-01
                      9958-X        0-F    13933-X        0-F  1.75E+09
    0.00E+00  0.00E+00               ( 1)
                    4.92E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.3350E-01

 ITE=  7  3.68E+08  2.16E+09   0.00E+00   6.93E+00   0.00E+00  1.23E+09
7.78E-01  2.70E+04  6.87E-02  7.36E-01  1.00E+00  9.57E-01
                     14009-X        0-F    13933-X        0-F  1.67E+09
    0.00E+00  0.00E+00               ( 1)
                    4.47E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1083E+00

 ITE=  8  1.92E+09  2.15E+09   0.00E+00   6.82E+00   0.00E+00  1.23E+09
4.06E+00  2.69E+04  6.77E-02  6.64E-01  1.00E+00  2.77E+00
                     14002-X        0-F    14009-X        0-F  1.86E+09
    0.00E+00  0.00E+00               ( 1)
                   -5.18E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.9234E-01

 ITE=  9 -1.30E+08  1.82E+09   0.00E+00   4.33E+00   0.00E+00  1.48E+09
-2.74E-01  2.27E+04  4.30E-02  1.06E+00  1.00E+00  3.89E-02
                     13939-X        0-F    14010-X        0-F  1.39E+09
    0.00E+00  0.00E+00               ( 1)
                    4.89E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4182E-01

 ITE= 10  1.34E+09  1.95E+09   0.00E+00   5.93E+00   0.00E+00  1.42E+09
2.83E+00  2.43E+04  5.88E-02  8.37E-01  1.00E+00 -4.35E+00
                     14002-X        0-F    14002-X        0-F  1.70E+09
```

```
    0.00E+00  0.00E+00              ( 1)
                   -5.36E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.7958E-01

 ITE= 11  4.08E+08  1.72E+09   0.00E+00   3.48E+00   0.00E+00  1.15E+09
8.62E-01  2.16E+04  3.45E-02  7.33E-01  1.00E+00  4.62E-01
                     13939-X        0-F    13939-X        0-F  1.57E+09
    0.00E+00  0.00E+00              ( 1)
                    4.07E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.3877E-01

 ITE= 12  7.63E+08  1.57E+09   0.00E+00   5.35E+00   0.00E+00  8.70E+08
1.61E+00  1.96E+04  5.31E-02  6.84E-01  1.00E+00  1.76E-01
                      9965-X        0-F    13939-X        0-F  1.27E+09
    0.00E+00  0.00E+00              ( 1)
                   -3.66E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1069E+00

 ITE= 13  3.62E+08  1.48E+09   0.00E+00   2.38E+00   0.00E+00  7.60E+08
7.65E-01  1.85E+04  2.36E-02  6.04E-01  1.00E+00  9.47E-01
                     13939-X        0-F    14009-X        0-F  1.26E+09
    0.00E+00  0.00E+00              ( 1)
                    3.54E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.3656E-01

 ITE= 14  3.58E+08  1.40E+09   0.00E+00   4.81E+00   0.00E+00  6.23E+08
7.57E-01  1.76E+04  4.77E-02  5.31E-01  1.00E+00  9.49E-01
                     13939-X        0-F    14006-Z        0-F  1.18E+09
    0.00E+00  0.00E+00              ( 1)
                    3.44E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.6597E-01

 ITE= 15  4.82E+08  1.25E+09   0.00E+00   6.82E+00   0.00E+00  7.78E+08
1.02E+00  1.57E+04  6.77E-02  7.42E-01  1.00E+00  1.05E-01
                      9965-X        0-F    14010-X        0-F  1.05E+09
    0.00E+00  0.00E+00              ( 1)
                   -2.79E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1041E+00


 RESTART FOR AUTOMATIC-TIME-STEPPING AFTER ITERATION   15


      ITERATION LIMIT HAS BEEN REACHED, ITEMAX =   15

      DISPLACEMENTS WERE SCALED DOWN DUE TO LIMITING DISPLACEMENT FEATURE


      REFERENCE CONVERGENCE NORMS USED:  DISPLACEMENT = 1.008E+02,  FORCE =
7.996E+04


 I T E R A T I O N   T I M E   L O G

 SOLUTION TIME (SECONDS)   . . . . . . . . . . . . . . . . . . . . . =     178.26

 PERCENT OF TIME SPENT IN LINE SEARCHING . . . . . . . . . . . . . . . . =   0.00
 PERCENT OF TIME SPENT IN LOAD VECTOR/STIFFNESS MATRIX CALCULATION . =  14.09
 PERCENT OF TIME SPENT IN SOLUTION OF EQUATIONS  . . . . . . . . . . =  85.91


 METHOD  STEP-NUMBER  SUBINCREMENT    TIME STEP    SOLUTION TIME   INITIAL
ENERGY
 *ATS*          1          1       0.100000E+00     0.100000E+00
0.239980E+05
```

```
 I N T E R M E D I A T E   P R I N T O U T   D U R I N G   E Q U I L I B R I U M
  I T E R A T I O N S


          OUT-OF-         NORM OF
CONVERGENCE RATIOS  CONVERGENCE RATIOS   OUT-OF-BALANCE LOAD
          BALANCE     OUT-OF-BALANCE        NORM OF INCREMENTAL         FOR
OUT-OF-BALANCE    FOR INCREMENTAL    VECTOR CALCULATION
          ENERGY      FORCE    MOMENT      DISP.      ROTN.    CFORCE
ENERGY     FORCE    DISP.     CFORCE      BETA      RATIO
                   NODE-DOF   NODE-DOF   NODE-DOF   NODE-DOF   CFNORM
     MOMENT   ROTN.                (ITERNS)
                  MAX VALUE  MAX VALUE  MAX VALUE  MAX VALUE

COMPARE WITH        COMPARE WITH
                                                                                ETOL
      RTOL     DTOL      RCTOL

1.00E-03 (NOT USED)(NOT USED) 5.00E-02

 ITE=  0  2.40E+04  4.00E+04   0.00E+00   6.44E+01   0.00E+00  4.63E+09
1.00E+00  1.00E+00  8.03E+00  4.63E+11
                     12347-Z        0-F    14006-X        0-F  0.00E+00
    0.00E+00  0.00E+00
                   1.55E+03   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1564E+00

 ITE=  1  1.34E+09  2.86E+09   0.00E+00   1.01E+02   0.00E+00  7.76E+08
1.00E+00  7.15E+04  1.00E+00  1.38E+00  1.00E+00  3.46E+05
                     10002-X        0-F    13613-Y        0-F  5.63E+08
    0.00E+00  0.00E+00               ( 1)
                   5.22E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1669E+00

 ITE=  2 -7.88E+08  2.70E+09   0.00E+00   6.46E+00   0.00E+00  1.18E+09
-5.88E-01  6.75E+04  6.41E-02  9.42E-01  1.00E+00 -3.11E-01
                     14006-X        0-F    13936-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                   5.64E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4530E-01

 ITE=  3 -4.34E+07  2.47E+09   0.00E+00   3.66E+00   0.00E+00  8.96E+08
-3.24E-02  6.18E+04  3.63E-02  7.15E-01  1.00E+00  1.12E+00
                     14006-X        0-F    14005-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                   5.44E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2294E-01

 ITE=  4 -2.94E+08  2.33E+09   0.00E+00   2.27E+00   0.00E+00  8.59E+08
-2.20E-01  5.84E+04  2.25E-02  6.08E-01  1.00E+00 -1.04E+01
                     14006-X        0-F    14006-X        0-F  1.41E+09
    0.00E+00  0.00E+00               ( 1)
                   5.14E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1660E-01

 ITE=  5  1.22E+09  2.34E+09   0.00E+00   5.19E+00   0.00E+00  6.80E+08
9.09E-01  5.86E+04  5.15E-02  4.40E-01  1.00E+00  1.06E-01
                     13930-X        0-F    13935-X        0-F  1.55E+09
    0.00E+00  0.00E+00               ( 1)
                   5.10E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.7821E-01

 ITE=  6  1.88E+09  2.34E+09   0.00E+00   6.24E+00   0.00E+00  1.43E+09
1.41E+00  5.85E+04  6.19E-02  7.46E-01  1.00E+00  7.26E-01
                     14002-X        0-F    13933-X        0-F  1.92E+09
    0.00E+00  0.00E+00               ( 1)
                  -5.62E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.9558E-01
```

```
 ITE=  7  6.04E+08  1.98E+09   0.00E+00   4.63E+00   0.00E+00  1.19E+09
4.51E-01  4.96E+04  4.59E-02  7.44E-01  1.00E+00  3.88E-01
                     14002-X        0-F    14009-X        0-F  1.59E+09
    0.00E+00  0.00E+00               ( 1)
                   -5.14E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5980E-01

 ITE=  8  1.04E+09  2.02E+09   0.00E+00   3.81E+00   0.00E+00  9.00E+08
7.75E-01  5.05E+04  3.78E-02  5.18E-01  1.00E+00  1.55E+00
                     14002-X        0-F    13939-X        0-F  1.74E+09
    0.00E+00  0.00E+00               ( 1)
                   -6.44E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5646E-01

 ITE=  9  5.91E+08  1.64E+09   0.00E+00   3.32E+00   0.00E+00  9.99E+08
4.41E-01  4.09E+04  3.29E-02  7.05E-01  1.00E+00  1.99E-01
                     14009-X        0-F    13940-X        0-F  1.42E+09
    0.00E+00  0.00E+00               ( 1)
                    2.87E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.3698E-01

 ITE= 10  4.21E+08  1.58E+09   0.00E+00   2.74E+00   0.00E+00  8.63E+07
3.14E-01  3.95E+04  2.72E-02  6.28E-02  1.00E+00  8.70E-01
                      9938-Z        0-F    13940-X        0-F  1.37E+09
    0.00E+00  0.00E+00               ( 1)
                    2.70E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.3461E-01

 ITE= 11  4.58E+08  1.55E+09   0.00E+00   3.44E+00   0.00E+00  2.25E+08
3.42E-01  3.87E+04  3.41E-02  1.67E-01  1.00E+00  9.89E-01
                      9938-Z        0-F    13940-X        0-F  1.35E+09
    0.00E+00  0.00E+00               ( 1)
                    2.67E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.8033E-01

 ITE= 12  3.88E+08  1.53E+09   0.00E+00   2.75E+00   0.00E+00  3.70E+08
2.90E-01  3.84E+04  2.73E-02  2.82E-01  1.00E+00  1.20E+00
                      9962-X        0-F    14006-X        0-F  1.31E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.79E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5737E-01

 ITE= 13  9.30E+08  1.56E+09   0.00E+00   5.27E+00   0.00E+00  6.64E+08
6.94E-01  3.89E+04  5.23E-02  5.11E-01  1.00E+00  1.33E+00
                      9962-X        0-F    14006-Z        0-F  1.30E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.53E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1212E+00

 ITE= 14  5.36E+07  1.29E+09   0.00E+00   3.59E+00   0.00E+00  7.09E+08
4.00E-02  3.22E+04  3.57E-02  7.25E-01  1.00E+00  8.44E-02
                      9962-X        0-F    14007-X        0-F  9.78E+08
    0.00E+00  0.00E+00               ( 1)
                   -3.02E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.7422E-01

 ITE= 15  3.87E+08  1.18E+09   0.00E+00   6.97E+00   0.00E+00  2.73E+08
2.89E-01  2.96E+04  6.91E-02  3.05E-01  1.00E+00  9.86E-01
                      9962-X        0-F     9994-X        0-F  8.95E+08
    0.00E+00  0.00E+00               ( 1)
                   -2.76E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1544E+00


 RESTART FOR AUTOMATIC-TIME-STEPPING AFTER ITERATION   15
```

```
      ITERATION LIMIT HAS BEEN REACHED, ITEMAX =   15

      DISPLACEMENTS WERE SCALED DOWN DUE TO LIMITING DISPLACEMENT FEATURE


      REFERENCE CONVERGENCE NORMS USED:  DISPLACEMENT = 1.008E+02,  FORCE =
3.998E+04


 I T E R A T I O N   T I M E   L O G

 SOLUTION TIME (SECONDS)   . . . . . . . . . . . . . . . . . . . . =     180.70

 PERCENT OF TIME SPENT IN LINE SEARCHING . . . . . . . . . . . . . . . . =   0.00
 PERCENT OF TIME SPENT IN LOAD VECTOR/STIFFNESS MATRIX CALCULATION . =  14.39
 PERCENT OF TIME SPENT IN SOLUTION OF EQUATIONS  . . . . . . . . . . =  85.61



 METHOD  STEP-NUMBER  SUBINCREMENT    TIME STEP    SOLUTION TIME   INITIAL
ENERGY
 *ATS*          1          1       0.500000E-01     0.500000E-01
0.120804E+05


 I N T E R M E D I A T E   P R I N T O U T   D U R I N G   E Q U I L I B R I U M
  I T E R A T I O N S


          OUT-OF-         NORM OF
CONVERGENCE RATIOS  CONVERGENCE RATIOS   OUT-OF-BALANCE LOAD
          BALANCE     OUT-OF-BALANCE        NORM OF INCREMENTAL         FOR
OUT-OF-BALANCE    FOR INCREMENTAL    VECTOR CALCULATION
          ENERGY      FORCE    MOMENT      DISP.      ROTN.    CFORCE
ENERGY     FORCE    DISP.     CFORCE      BETA      RATIO
                    NODE-DOF   NODE-DOF   NODE-DOF   NODE-DOF   CFNORM
     MOMENT   ROTN.               (ITERNS)
                   MAX VALUE  MAX VALUE  MAX VALUE  MAX VALUE

COMPARE WITH        COMPARE WITH
                                                                          ETOL
      RTOL     DTOL      RCTOL

1.00E-03 (NOT USED)(NOT USED) 5.00E-02

 ITE=  0  1.21E+04  2.00E+04   0.00E+00   6.44E+01   0.00E+00  4.63E+09
1.00E+00  1.00E+00  8.03E+00  4.63E+11
                     12347-Z        0-F    14006-X        0-F  0.00E+00
    0.00E+00  0.00E+00
                    7.74E+02   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1564E+00

 ITE=  1  1.34E+09  2.86E+09   0.00E+00   1.01E+02   0.00E+00  7.76E+08
1.00E+00  1.43E+05  1.00E+00  1.38E+00  1.00E+00  6.87E+05
                     10002-X        0-F    13613-Y        0-F  5.63E+08
    0.00E+00  0.00E+00               ( 1)
                    5.22E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1669E+00

 ITE=  2 -7.92E+08  2.70E+09   0.00E+00   6.44E+00   0.00E+00  1.18E+09
-5.91E-01  1.35E+05  6.39E-02  9.42E-01  1.00E+00 -3.11E-01
                     14006-X        0-F    13936-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                    5.64E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4568E-01

 ITE=  3 -3.19E+07  2.47E+09   0.00E+00   3.68E+00   0.00E+00  8.96E+08
-2.38E-02  1.24E+05  3.65E-02  7.15E-01  1.00E+00  1.12E+00
```

```
                    14006-X        0-F    14005-X        0-F  1.25E+09
   0.00E+00  0.00E+00              ( 1)
                   5.43E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2232E-01

 ITE=  4 -3.02E+08  2.33E+09   0.00E+00   2.18E+00   0.00E+00  8.59E+08
-2.25E-01  1.17E+05  2.17E-02  6.09E-01  1.00E+00 -1.46E+01
                    14006-X        0-F    14006-X        0-F  1.41E+09
   0.00E+00  0.00E+00              ( 1)
                   5.16E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1535E-01

 ITE=  5  1.81E+09  2.35E+09   0.00E+00   8.45E+00   0.00E+00  6.81E+08
1.35E+00  1.18E+05  8.39E-02  4.40E-01  1.00E+00  1.63E-01
                    13930-X        0-F    13935-X        0-F  1.55E+09
   0.00E+00  0.00E+00              ( 1)
                   5.11E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1316E+00

 ITE=  6  2.20E+09  2.24E+09   0.00E+00   6.67E+00   0.00E+00  1.31E+09
1.64E+00  1.12E+05  6.61E-02  7.16E-01  1.00E+00  1.17E+00
                    13939-X        0-F    13933-X        0-F  1.84E+09
   0.00E+00  0.00E+00              ( 1)
                   5.15E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1136E+00

 ITE=  7  3.17E+08  1.76E+09   0.00E+00   4.14E+00   0.00E+00  1.45E+09
2.37E-01  8.81E+04  4.11E-02  9.50E-01  1.00E+00  2.46E-01
                     9965-X        0-F    13940-X        0-F  1.53E+09
   0.00E+00  0.00E+00              ( 1)
                  -3.51E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.3721E-01

 ITE=  8  1.03E+09  1.78E+09   0.00E+00   4.90E+00   0.00E+00  7.41E+08
7.68E-01  8.90E+04  4.86E-02  4.79E-01  1.00E+00  1.51E+00
                     9965-X        0-F    13939-X        0-F  1.55E+09
   0.00E+00  0.00E+00              ( 1)
                  -4.16E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1032E+00

 ITE=  9  2.58E+08  1.57E+09   0.00E+00   3.73E+00   0.00E+00  5.38E+08
1.92E-01  7.85E+04  3.70E-02  3.79E-01  1.00E+00  4.60E-01
                     9965-X        0-F    13930-Z        0-F  1.42E+09
   0.00E+00  0.00E+00              ( 1)
                  -3.59E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.6261E-01

 ITE= 10  8.29E+08  1.60E+09   0.00E+00   6.11E+00   0.00E+00  5.29E+08
6.19E-01  7.99E+04  6.06E-02  3.67E-01  1.00E+00  1.15E+00
                     9965-X        0-F    13939-X        0-F  1.44E+09
   0.00E+00  0.00E+00              ( 1)
                  -3.29E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1041E+00

 ITE= 11 -5.12E+07  1.37E+09   0.00E+00   2.19E+00   0.00E+00  7.39E+08
-3.82E-02  6.87E+04  2.17E-02  6.35E-01  1.00E+00  7.30E-02
                     9965-X        0-F    14007-X        0-F  1.16E+09
   0.00E+00  0.00E+00              ( 1)
                  -2.93E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1257E-01

 ITE= 12 -4.43E+07  1.36E+09   0.00E+00   2.24E+00   0.00E+00  7.86E+07
-3.30E-02  6.79E+04  2.22E-02  6.82E-02  1.00E+00  7.24E-01
                     9965-X        0-F    14009-X        0-F  1.15E+09
   0.00E+00  0.00E+00              ( 1)
                  -2.88E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1800E-01
```

```
 ITE= 13 -5.68E+07  1.30E+09   0.00E+00   1.93E+00   0.00E+00  1.98E+08
-4.24E-02  6.52E+04  1.91E-02  1.78E-01  1.00E+00  5.29E-01
                      9965-X        0-F    14009-X        0-F  1.12E+09
    0.00E+00  0.00E+00              ( 1)
                  -2.81E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1747E-01

 ITE= 14  2.80E+08  1.27E+09   0.00E+00   4.73E+00   0.00E+00  3.48E+08
2.09E-01  6.37E+04  4.69E-02  3.33E-01  1.00E+00  1.19E+00
                      9965-X        0-F    14009-X        0-F  1.05E+09
    0.00E+00  0.00E+00              ( 1)
                  -2.74E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.7225E-01

 ITE= 15 -2.75E+07  1.19E+09   0.00E+00   3.43E+00   0.00E+00  1.04E+08
-2.05E-02  5.97E+04  3.40E-02  1.07E-01  1.00E+00  9.17E-01
                      9965-X        0-F    10008-X        0-F  9.79E+08
    0.00E+00  0.00E+00              ( 1)
                  -2.50E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5727E-01


 RESTART FOR AUTOMATIC-TIME-STEPPING AFTER ITERATION   15


      ITERATION LIMIT HAS BEEN REACHED, ITEMAX =   15

      DISPLACEMENTS WERE SCALED DOWN DUE TO LIMITING DISPLACEMENT FEATURE


      REFERENCE CONVERGENCE NORMS USED:  DISPLACEMENT = 1.008E+02,  FORCE =
1.999E+04


 I T E R A T I O N   T I M E   L O G

 SOLUTION TIME (SECONDS)   . . . . . . . . . . . . . . . . . . . . . =     181.25

 PERCENT OF TIME SPENT IN LINE SEARCHING . . . . . . . . . . . . . . . . =   0.00
 PERCENT OF TIME SPENT IN LOAD VECTOR/STIFFNESS MATRIX CALCULATION . =  14.16
 PERCENT OF TIME SPENT IN SOLUTION OF EQUATIONS  . . . . . . . . . . =  85.84


 METHOD  STEP-NUMBER  SUBINCREMENT    TIME STEP    SOLUTION TIME   INITIAL
ENERGY
 *ATS*          1          1       0.250000E-01     0.250000E-01
0.606058E+04


 I N T E R M E D I A T E   P R I N T O U T   D U R I N G   E Q U I L I B R I U M
  I T E R A T I O N S


          OUT-OF-         NORM OF
CONVERGENCE RATIOS  CONVERGENCE RATIOS   OUT-OF-BALANCE LOAD
          BALANCE     OUT-OF-BALANCE        NORM OF INCREMENTAL         FOR
OUT-OF-BALANCE    FOR INCREMENTAL    VECTOR CALCULATION
          ENERGY      FORCE    MOMENT      DISP.      ROTN.    CFORCE
ENERGY     FORCE    DISP.     CFORCE      BETA      RATIO
                   NODE-DOF   NODE-DOF   NODE-DOF   NODE-DOF   CFNORM
     MOMENT   ROTN.                (ITERNS)
                  MAX VALUE  MAX VALUE  MAX VALUE  MAX VALUE

COMPARE WITH        COMPARE WITH
                                                                          ETOL
      RTOL     DTOL      RCTOL
```

```
1.00E-03 (NOT USED)(NOT USED) 5.00E-02

 ITE=  0  6.06E+03  1.00E+04   0.00E+00   6.44E+01   0.00E+00  4.63E+09
1.00E+00  1.00E+00  8.03E+00  4.63E+11
                     12347-Z        0-F    14006-X        0-F  0.00E+00
    0.00E+00  0.00E+00
                   3.87E+02   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1564E+00

 ITE=  1  1.34E+09  2.86E+09   0.00E+00   1.01E+02   0.00E+00  7.76E+08
1.00E+00  2.86E+05  1.00E+00  1.38E+00  1.00E+00  1.37E+06
                     10002-X        0-F    13613-Y        0-F  5.63E+08
    0.00E+00  0.00E+00               ( 1)
                   5.22E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1670E+00

 ITE=  2 -7.94E+08  2.70E+09   0.00E+00   6.44E+00   0.00E+00  1.18E+09
-5.92E-01  2.70E+05  6.39E-02  9.42E-01  1.00E+00 -3.11E-01
                     14006-X        0-F    13936-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                   5.64E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4590E-01

 ITE=  3 -2.87E+07  2.47E+09   0.00E+00   3.69E+00   0.00E+00  8.96E+08
-2.14E-02  2.47E+05  3.66E-02  7.15E-01  1.00E+00  1.11E+00
                     14006-X        0-F    14005-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                   5.43E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2218E-01

 ITE=  4 -3.05E+08  2.33E+09   0.00E+00   2.16E+00   0.00E+00  8.59E+08
-2.28E-01  2.34E+05  2.14E-02  6.09E-01  1.00E+00 -1.63E+01
                     14006-X        0-F    14006-X        0-F  1.41E+09
    0.00E+00  0.00E+00               ( 1)
                   5.17E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1492E-01

 ITE=  5  1.92E+09  2.35E+09   0.00E+00   9.10E+00   0.00E+00  6.81E+08
1.43E+00  2.35E+05  9.03E-02  4.40E-01  1.00E+00  1.83E-01
                     13930-X        0-F    13935-X        0-F  1.55E+09
    0.00E+00  0.00E+00               ( 1)
                   5.12E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1418E+00

 ITE=  6  2.29E+09  2.22E+09   0.00E+00   6.93E+00   0.00E+00  1.30E+09
1.71E+00  2.22E+05  6.88E-02  7.17E-01  1.00E+00  1.11E+00
                     13939-X        0-F    14006-X        0-F  1.82E+09
    0.00E+00  0.00E+00               ( 1)
                   5.06E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1165E+00

 ITE=  7 -1.03E+08  1.74E+09   0.00E+00   2.80E+00   0.00E+00  1.44E+09
-7.67E-02  1.74E+05  2.78E-02  9.53E-01  1.00E+00  2.61E-01
                      9965-X        0-F    13940-X        0-F  1.51E+09
    0.00E+00  0.00E+00               ( 1)
                  -3.60E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1205E-01

 ITE=  8  1.03E+09  1.82E+09   0.00E+00   5.36E+00   0.00E+00  5.77E+08
7.67E-01  1.82E+05  5.31E-02  3.75E-01  1.00E+00 -1.33E+00
                     13939-X        0-F     9958-X        0-F  1.54E+09
    0.00E+00  0.00E+00               ( 1)
                   4.45E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.8651E-01

 ITE=  9  5.76E+08  1.72E+09   0.00E+00   5.38E+00   0.00E+00  5.25E+08
4.30E-01  1.72E+05  5.34E-02  3.48E-01  1.00E+00  6.23E-01
                     13939-X        0-F    13939-X        0-F  1.51E+09
```

```
    0.00E+00  0.00E+00                ( 1)
                     4.31E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1044E+00

 ITE= 10  5.16E+08  1.58E+09   0.00E+00   4.56E+00   0.00E+00  7.06E+08
3.85E-01  1.59E+05  4.53E-02  4.97E-01  1.00E+00  1.23E+00
                      9965-X        0-F    13935-X        0-F  1.42E+09
    0.00E+00  0.00E+00                ( 1)
                    -3.33E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.6474E-01

 ITE= 11  2.23E+08  1.41E+09   0.00E+00   1.73E+00   0.00E+00  6.50E+08
1.66E-01  1.41E+05  1.71E-02  5.25E-01  1.00E+00  9.30E-01
                      9965-X        0-F    14009-X        0-F  1.24E+09
    0.00E+00  0.00E+00                ( 1)
                    -3.04E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1771E-01

 ITE= 12  8.39E+07  1.39E+09   0.00E+00   3.17E+00   0.00E+00  1.11E+08
6.26E-02  1.39E+05  3.14E-02  9.08E-02  1.00E+00  1.11E+00
                      9965-X        0-F    14009-X        0-F  1.22E+09
    0.00E+00  0.00E+00                ( 1)
                    -2.97E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5375E-01

 ITE= 13  3.53E+08  1.31E+09   0.00E+00   6.01E+00   0.00E+00  6.79E+08
2.63E-01  1.31E+05  5.96E-02  6.02E-01  1.00E+00  2.18E+00
                      9965-X        0-F    13976-X        0-F  1.13E+09
    0.00E+00  0.00E+00                ( 1)
                    -2.76E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1062E+00

 ITE= 14 -6.65E+07  1.09E+09   0.00E+00   4.46E+00   0.00E+00  5.64E+08
-4.96E-02  1.09E+05  4.43E-02  6.30E-01  1.00E+00 -2.67E-02
                      9965-X        0-F    14007-X        0-F  8.94E+08
    0.00E+00  0.00E+00                ( 1)
                    -2.43E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.8258E-01

 ITE= 15 -6.95E+06  1.06E+09   0.00E+00   5.59E+00   0.00E+00  3.26E+08
-5.19E-03  1.06E+05  5.55E-02  3.67E-01  1.00E+00  2.05E-01
                      9965-X        0-F    13976-Z        0-F  8.87E+08
    0.00E+00  0.00E+00                ( 1)
                    -2.20E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5457E-01


 RESTART FOR AUTOMATIC-TIME-STEPPING AFTER ITERATION   15


      ITERATION LIMIT HAS BEEN REACHED, ITEMAX =   15

      DISPLACEMENTS WERE SCALED DOWN DUE TO LIMITING DISPLACEMENT FEATURE


      REFERENCE CONVERGENCE NORMS USED:  DISPLACEMENT = 1.008E+02,  FORCE =
9.996E+03


 I T E R A T I O N   T I M E   L O G

 SOLUTION TIME (SECONDS)   . . . . . . . . . . . . . . . . . . . . =     181.03

 PERCENT OF TIME SPENT IN LINE SEARCHING . . . . . . . . . . . . . . . . =   0.00
 PERCENT OF TIME SPENT IN LOAD VECTOR/STIFFNESS MATRIX CALCULATION . =  14.40
 PERCENT OF TIME SPENT IN SOLUTION OF EQUATIONS  . . . . . . . . . . . =  85.60
```

```
 METHOD  STEP-NUMBER  SUBINCREMENT    TIME STEP    SOLUTION TIME   INITIAL
ENERGY
 *ATS*          1          1       0.200000E-01     0.200000E-01
0.485172E+04


 I N T E R M E D I A T E   P R I N T O U T   D U R I N G   E Q U I L I B R I U M
  I T E R A T I O N S


          OUT-OF-         NORM OF
CONVERGENCE RATIOS  CONVERGENCE RATIOS   OUT-OF-BALANCE LOAD
          BALANCE     OUT-OF-BALANCE        NORM OF INCREMENTAL         FOR
OUT-OF-BALANCE    FOR INCREMENTAL    VECTOR CALCULATION
          ENERGY      FORCE    MOMENT      DISP.      ROTN.    CFORCE
ENERGY     FORCE    DISP.     CFORCE      BETA      RATIO
                    NODE-DOF   NODE-DOF   NODE-DOF   NODE-DOF   CFNORM
     MOMENT   ROTN.               (ITERNS)
                   MAX VALUE  MAX VALUE  MAX VALUE  MAX VALUE

COMPARE WITH        COMPARE WITH
                                                                                ETOL
      RTOL     DTOL      RCTOL

1.00E-03 (NOT USED)(NOT USED) 5.00E-02

 ITE=  0  4.85E+03  8.00E+03   0.00E+00   6.44E+01   0.00E+00  4.63E+09
1.00E+00  1.00E+00  8.03E+00  4.63E+11
                     12347-Z        0-F    14006-X        0-F  0.00E+00
    0.00E+00  0.00E+00
                    3.10E+02   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1564E+00

 ITE=  1  1.34E+09  2.86E+09   0.00E+00   1.01E+02   0.00E+00  7.76E+08
1.00E+00  3.57E+05  1.00E+00  1.38E+00  1.00E+00  1.71E+06
                     10002-X        0-F    13613-Y        0-F  5.63E+08
    0.00E+00  0.00E+00               ( 1)
                    5.22E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1670E+00

 ITE=  2 -7.94E+08  2.70E+09   0.00E+00   6.44E+00   0.00E+00  1.18E+09
-5.93E-01  3.37E+05  6.39E-02  9.42E-01  1.00E+00 -3.11E-01
                     14006-X        0-F    13936-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                    5.64E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4594E-01

 ITE=  3 -2.74E+07  2.47E+09   0.00E+00   3.69E+00   0.00E+00  8.96E+08
-2.05E-02  3.09E+05  3.66E-02  7.15E-01  1.00E+00  1.11E+00
                     14006-X        0-F    14005-X        0-F  1.25E+09
    0.00E+00  0.00E+00               ( 1)
                    5.43E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2212E-01

 ITE=  4 -3.07E+08  2.33E+09   0.00E+00   2.15E+00   0.00E+00  8.59E+08
-2.29E-01  2.92E+05  2.14E-02  6.09E-01  1.00E+00 -1.72E+01
                     14006-X        0-F    14006-X        0-F  1.41E+09
    0.00E+00  0.00E+00               ( 1)
                    5.17E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1479E-01

 ITE=  5  2.02E+09  2.35E+09   0.00E+00   9.66E+00   0.00E+00  6.81E+08
1.50E+00  2.94E+05  9.58E-02  4.40E-01  1.00E+00  1.89E-01
                     13930-X        0-F    13935-X        0-F  1.55E+09
    0.00E+00  0.00E+00               ( 1)
                    5.12E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1507E+00
```

```
 ITE=  6  2.13E+09  2.21E+09   0.00E+00   6.56E+00   0.00E+00  1.29E+09
1.59E+00  2.76E+05  6.51E-02  7.18E-01  1.00E+00  1.05E+00
                     13939-X        0-F    14006-X        0-F  1.80E+09
    0.00E+00  0.00E+00               ( 1)
                    4.98E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1112E+00

 ITE=  7  3.62E+08  1.74E+09   0.00E+00   3.28E+00   0.00E+00  1.43E+09
2.70E-01  2.17E+05  3.25E-02  9.50E-01  1.00E+00  2.57E-01
                      9965-X        0-F    13939-X        0-F  1.50E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.71E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2679E-01

 ITE=  8  9.18E+08  1.67E+09   0.00E+00   5.45E+00   0.00E+00  8.52E+08
6.85E-01  2.08E+05  5.41E-02  6.17E-01  1.00E+00  6.63E-01
                      9994-X        0-F    14006-X        0-F  1.38E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.31E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1215E+00

 ITE=  9  7.66E+08  1.59E+09   0.00E+00   6.95E+00   0.00E+00  5.52E+08
5.72E-01  1.99E+05  6.89E-02  4.08E-01  1.00E+00  1.09E+00
                     14006-Z        0-F    14007-X        0-F  1.35E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.25E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1435E+00

 ITE= 10  2.38E+08  1.36E+09   0.00E+00   6.48E+00   0.00E+00  8.45E+08
1.77E-01  1.70E+05  6.42E-02  7.54E-01  1.00E+00 -5.75E-02
                      9965-X        0-F    13930-Z        0-F  1.12E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.12E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2519E-01

 ITE= 11  7.77E+08  1.31E+09   0.00E+00   5.29E+00   0.00E+00  5.51E+08
5.80E-01  1.64E+05  5.25E-02  5.51E-01  1.00E+00  3.93E-01
                      9965-X        0-F    13976-Z        0-F  1.00E+09
    0.00E+00  0.00E+00               ( 1)
                   -3.02E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1173E+00

 ITE= 12  1.95E+08  1.17E+09   0.00E+00   2.91E+00   0.00E+00  5.30E+08
1.45E-01  1.46E+05  2.89E-02  5.23E-01  1.00E+00  7.88E-01
                      9965-X        0-F    13976-Z        0-F  1.01E+09
    0.00E+00  0.00E+00               ( 1)
                   -2.61E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4206E-01

 ITE= 13 -1.51E+07  1.09E+09   0.00E+00   1.77E+00   0.00E+00  5.67E+08
-1.13E-02  1.36E+05  1.75E-02  7.02E-01  1.00E+00  9.38E-02
                      9965-X        0-F    13976-Z        0-F  8.07E+08
    0.00E+00  0.00E+00               ( 1)
                   -2.49E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1410E-01

 ITE= 14  2.24E+07  1.10E+09   0.00E+00   2.31E+00   0.00E+00  2.93E+08
1.67E-02  1.38E+05  2.29E-02  3.46E-01  1.00E+00 -1.83E+00
                      9965-X        0-F    13978-Z        0-F  8.48E+08
    0.00E+00  0.00E+00               ( 1)
                   -2.45E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2057E-01

 ITE= 15  3.19E+06  1.08E+09   0.00E+00   2.14E+00   0.00E+00  2.42E+07
2.38E-03  1.35E+05  2.12E-02  2.91E-02  1.00E+00  5.89E-01
                      9965-X        0-F    13978-Z        0-F  8.33E+08
    0.00E+00  0.00E+00               ( 1)
```

```
                    -2.39E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1067E-02


 RESTART FOR AUTOMATIC-TIME-STEPPING AFTER ITERATION   15


      ITERATION LIMIT HAS BEEN REACHED, ITEMAX =   15

      DISPLACEMENTS WERE SCALED DOWN DUE TO LIMITING DISPLACEMENT FEATURE


      REFERENCE CONVERGENCE NORMS USED:  DISPLACEMENT = 1.008E+02,  FORCE =
7.996E+03


 I T E R A T I O N   T I M E   L O G

 SOLUTION TIME (SECONDS)   . . . . . . . . . . . . . . . . . . . . =     184.54

 PERCENT OF TIME SPENT IN LINE SEARCHING . . . . . . . . . . . . . . . . =   0.00
 PERCENT OF TIME SPENT IN LOAD VECTOR/STIFFNESS MATRIX CALCULATION . =  14.23
 PERCENT OF TIME SPENT IN SOLUTION OF EQUATIONS  . . . . . . . . . . =  85.77



 METHOD  STEP-NUMBER  SUBINCREMENT    TIME STEP    SOLUTION TIME   INITIAL
ENERGY
 *ATS*          1          1       0.400000E+00     0.400000E+00
0.920833E+05


 I N T E R M E D I A T E   P R I N T O U T   D U R I N G   E Q U I L I B R I U M
  I T E R A T I O N S


          OUT-OF-         NORM OF
CONVERGENCE RATIOS  CONVERGENCE RATIOS   OUT-OF-BALANCE LOAD
          BALANCE     OUT-OF-BALANCE        NORM OF INCREMENTAL         FOR
OUT-OF-BALANCE    FOR INCREMENTAL    VECTOR CALCULATION
          ENERGY      FORCE    MOMENT      DISP.      ROTN.    CFORCE
ENERGY     FORCE    DISP.     CFORCE      BETA      RATIO
                    NODE-DOF   NODE-DOF   NODE-DOF   NODE-DOF   CFNORM
     MOMENT   ROTN.                (ITERNS)
                   MAX VALUE  MAX VALUE  MAX VALUE  MAX VALUE

COMPARE WITH        COMPARE WITH                                                    ETOL
      RTOL     DTOL      RCTOL

1.00E-03 (NOT USED)(NOT USED) 5.00E-02

 ITE=  0  9.21E+04  1.60E+05   0.00E+00   6.44E+01   0.00E+00  4.63E+09
1.00E+00  1.00E+00  8.03E+00  4.63E+11
                     12347-Z        0-F    14006-X        0-F  0.00E+00
    0.00E+00  0.00E+00
                    6.19E+03   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1564E+00

 ITE=  1  1.34E+09  2.86E+09   0.00E+00   1.01E+02   0.00E+00  7.75E+08
1.00E+00  1.79E+04  1.00E+00  1.38E+00  1.00E+00  9.00E+04
                     10002-X        0-F    13613-Y        0-F  5.63E+08
    0.00E+00  0.00E+00               ( 1)
                    5.22E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1667E+00

 ITE=  2 -7.75E+08  2.70E+09   0.00E+00   6.52E+00   0.00E+00  1.18E+09
-5.80E-01  1.69E+04  6.47E-02  9.42E-01  1.00E+00 -3.12E-01
```

```
                    14006-X        0-F    13936-X        0-F  1.25E+09
   0.00E+00  0.00E+00              ( 1)
                   5.64E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4420E-01

 ITE=  3 -8.59E+07  2.47E+09   0.00E+00   3.59E+00   0.00E+00  8.97E+08
-6.43E-02  1.55E+04  3.56E-02  7.14E-01  1.00E+00  1.14E+00
                    14006-X        0-F    14005-X        0-F  1.26E+09
   0.00E+00  0.00E+00              ( 1)
                   5.46E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.2414E-01

 ITE=  4 -2.84E+08  2.33E+09   0.00E+00   2.47E+00   0.00E+00  8.59E+08
-2.12E-01  1.46E+04  2.46E-02  6.08E-01  1.00E+00 -4.67E+00
                    14006-X        0-F    14004-X        0-F  1.41E+09
   0.00E+00  0.00E+00              ( 1)
                   5.08E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1972E-01

 ITE=  5  4.20E+08  2.33E+09   0.00E+00   1.70E+00   0.00E+00  6.78E+08
3.14E-01  1.46E+04  1.69E-02  4.40E-01  1.00E+00  1.00E-02
                    13930-X        0-F    13935-X        0-F  1.54E+09
   0.00E+00  0.00E+00              ( 1)
                   5.06E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5347E-02

 ITE=  6  1.62E+08  2.26E+09   0.00E+00   1.92E+00   0.00E+00  7.08E+08
1.21E-01  1.42E+04  1.91E-02  4.38E-01  1.00E+00  4.01E-01
                    13930-X        0-F    13934-X        0-F  1.62E+09
   0.00E+00  0.00E+00              ( 1)
                   5.03E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.4586E-02

 ITE=  7  9.59E+08  2.30E+09   0.00E+00   5.46E+00   0.00E+00  8.79E+08
7.17E-01  1.44E+04  5.42E-02  4.80E-01  1.00E+00  2.83E+00
                    13930-X        0-F    13933-X        0-F  1.83E+09
   0.00E+00  0.00E+00              ( 1)
                   5.01E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.8362E-01

 ITE=  8  2.03E+09  2.26E+09   0.00E+00   7.51E+00   0.00E+00  1.25E+09
1.52E+00  1.41E+04  7.45E-02  6.86E-01  1.00E+00  4.87E-01
                    14002-X        0-F    13940-X        0-F  1.82E+09
   0.00E+00  0.00E+00              ( 1)
                  -5.93E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1155E+00

 ITE=  9  5.52E+07  1.91E+09   0.00E+00   5.18E+00   0.00E+00  1.37E+09
4.13E-02  1.19E+04  5.14E-02  8.46E-01  1.00E+00  2.02E-01
                    13939-X        0-F    14006-X        0-F  1.62E+09
   0.00E+00  0.00E+00              ( 1)
                   4.79E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.8656E-01

 ITE= 10  1.67E+09  1.90E+09   0.00E+00   6.78E+00   0.00E+00  1.41E+09
1.25E+00  1.19E+04  6.72E-02  8.74E-01  1.00E+00  1.14E+01
                    14002-X        0-F    14002-X        0-F  1.61E+09
   0.00E+00  0.00E+00              ( 1)
                  -5.72E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.9853E-01

 ITE= 11  4.57E+08  1.60E+09   0.00E+00   4.30E+00   0.00E+00  1.20E+09
3.42E-01  1.00E+04  4.26E-02  8.46E-01  1.00E+00  2.62E-01
                    13939-X        0-F     9965-X        0-F  1.42E+09
   0.00E+00  0.00E+00              ( 1)
                   4.08E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.5523E-01
```

```
 ITE= 12  6.12E+08  1.62E+09   0.00E+00   3.51E+00   0.00E+00  9.36E+08
4.58E-01  1.01E+04  3.49E-02  7.42E-01  1.00E+00  4.96E-01
                     9965-X        0-F    13939-X        0-F  1.26E+09
    0.00E+00  0.00E+00              ( 1)
                  -3.67E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.8624E-01

 ITE= 13  2.05E+08  1.40E+09   0.00E+00   2.87E+00   0.00E+00  7.94E+08
1.53E-01  8.75E+03  2.85E-02  7.28E-01  1.00E+00  4.28E-01
                     9965-X        0-F    14006-X        0-F  1.09E+09
    0.00E+00  0.00E+00              ( 1)
                  -3.28E+08   0.00E+00  -1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.6357E-01

 ITE= 14  4.28E+08  1.38E+09   0.00E+00   5.25E+00   0.00E+00  6.11E+08
3.20E-01  8.66E+03  5.21E-02  5.12E-01  1.00E+00  1.55E+00
                     9965-X        0-F    13939-X        0-F  1.19E+09
    0.00E+00  0.00E+00              ( 1)
                  -3.01E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.1026E+00

 ITE= 15  2.49E+08  1.14E+09   0.00E+00   3.26E+00   0.00E+00  6.47E+08
1.86E-01  7.11E+03  3.24E-02  7.02E-01  1.00E+00 -1.02E-03
                     9965-X        0-F    13939-X        0-F  9.21E+08
    0.00E+00  0.00E+00              ( 1)
                  -2.64E+08   0.00E+00   1.20E+00   0.00E+00
 SCALING FACTOR DUE TO LIMITING DISPLACEMENTS:  0.9574E-01


 RESTART FOR AUTOMATIC-TIME-STEPPING AFTER ITERATION   15


      ITERATION LIMIT HAS BEEN REACHED, ITEMAX =   15

      DISPLACEMENTS WERE SCALED DOWN DUE TO LIMITING DISPLACEMENT FEATURE


      REFERENCE CONVERGENCE NORMS USED:  DISPLACEMENT = 1.008E+02,  FORCE =
1.599E+05


 I T E R A T I O N   T I M E   L O G

 SOLUTION TIME (SECONDS)   . . . . . . . . . . . . . . . . . . . . =     178.15

 PERCENT OF TIME SPENT IN LINE SEARCHING . . . . . . . . . . . . . . =   0.00
 PERCENT OF TIME SPENT IN LOAD VECTOR/STIFFNESS MATRIX CALCULATION . =  14.47
 PERCENT OF TIME SPENT IN SOLUTION OF EQUATIONS  . . . . . . . . . . =  85.53


     **** SOLUTION FAILED TO CONVERGE ****
     SOLUTION TIME STEP NUMBER ...........=         1
     TIME STEP SUBINCREMENT NUMBER .......=         1
     NUMBER OF ATTEMPTS MADE .............=         4
     LAST SOLUTION TIME STEP SUBINCREMENT =   0.200000E-01
     LAST CONVERGED SOLUTION TIME ........=   0.000000E+00


    96 EQUILIBRIUM ITERATIONS PERFORMED IN THIS TIME STEP TO REESTABLISH
EQUILIBRIUM
  STIFFNESS REFORMED FOR EVERY ITERATION OF THIS STEP
  NUMBER OF SUBINCREMENTS IN THIS TIME STEP =    6


    S T R E S S   C A L C U L A T I O N S
```

```
   S U M M A T I O N   O F   R E A C T I O N S  (X,Y,Z - GLOBAL COORDINATES)

FORCE-X =  0.0000000E+00   FORCE-Y =  0.0000000E+00   FORCE-Z =  0.0000000E+00


PROGRAM SOL601, build date: 04.11.2011    *** NO HEADING DEFINED ***


 S O L U T I O N   T I M E   L O G (IN SEC)

           FOR PROBLEM

 *** NO HEADING DEFINED ***



INPUT PHASE  . . . . . . . . . . . . . . . . . . .      1.73

SUBSTRUCTURES INPUT PHASE. . . . . . . . . . . .      0.00

INITIALIZATIONS. . . . . . . . . . . . . . . . .      0.45

ASSEMBLAGE OF LINEAR STIFFNESS,EFFECTIVE STIFF-
NESS,MASS MATRICES AND LOAD VECTORS . . . . . .       5.32

FREQUENCY (OR BUCKLING) ANALYSIS . . . . . . . .      0.00

INITIAL CALCULATIONS FOR MODE SUPERPOSITION
                     ANALYSIS . . . . . . . . .       0.00

TRIANGULARIZATION OF LINEAR (EFFECTIVE)
                     STIFFNESS MATRIX  . . . . .      0.00


STEP-BY-STEP SOLUTION (         1 TIME STEPS)

  CALCULATION OF EFFECTIVE LOAD VECTORS  . . .        0.00
  UPDATING EFFECTIVE STIFFNESS MATRICES
  AND RHS VECTOR FOR NONLINEARITIES  . . . . .      154.89
  UPDATING EFFECTIVE STIFFNESS MATRIX FOR
  CENTRIFUGAL DEFORMATION DEPENDENT LOADING. .        0.00
  MODE SUPERPOSITION . . . . . . . . . . . . .        0.00
  SOLUTION OF EQUATIONS  . . . . . . . . . . .      929.04
  EQUILIBRIUM ITERATIONS (TOTAL) . . . . . . .     1084.38
  CALCULATION AND PRINTING OF DISPLACE-
  MENTS, VELOCITIES, AND ACCELERATIONS . . . .    31777.94
  CALCULATION AND PRINTING OF STRESSES . . . .        1.90
  FRACTURE MECHANICS . . . . . . . . . . . . .        0.00

                              STEP-BY-STEP TOTAL. . .    1086.59

CALCULATION AND PRINTING OF SUBSTRUCTURE
                INTERNAL RESPONSES  . . . . . . . .       0.00



T O T A L   S O L U T I O N   T I M E (SEC) . . . . .    1095.29
MEMORY USED BY THE SPARSE SOLVER=    0.0mw (    0.0mb)
TOTAL MEMORY USED BY THE PROGRAM=   54.7mw (  437.5mb)
Checked in NX Nastran license feature nx_nas_advnlin_dsk.
*** END SOL 601 ***
*** FATAL ERROR: SOL 601 DID NOT FINISH SUCCESSFULLY.
*** ADVANCED NONLINEAR EXIT CODE 0 ***
*** ISHELL PROGRAM 'NXNA' COMPLETED ***
^^^ USER FATAL MESSAGE
^^^ ERROR IN ADVANCED NONLINEAR MODULE          0
```

```
 ^^^SOL601 FAILED
1
FEBRUARY  21, 2013  NX NASTRAN  5/18/11   PAGE     6


0

 * * * *  D B D I C T   P R I N T  * * * *      SUBDMAP = PRTSUM  ,  DMAP
STATEMENT NO.     29



0                                   * * * *  A N A L Y S I S  S U M M A R Y  T A
B L E  * * * *
0 SEID  PEID PROJ VERS APRCH      SEMG SEMR SEKR SELG SELR MODES DYNRED SOLLIN
PVALID SOLNL LOOPID DESIGN CYCLE SENSITIVITY

--------------------------------------------------------------------------------
-----------------------------------------
0SEID = SUPERELEMENT ID.
 PEID = PRIMARY SUPERELEMENT ID OF IMAGE SUPERELEMENT.
 PROJ = PROJECT ID NUMBER.
 VERS = VERSION ID.
 APRCH = BLANK FOR STRUCTURAL ANALYSIS.  HEAT FOR HEAT TRANSFER ANALYSIS.
 SEMG = STIFFNESS AND MASS MATRIX GENERATION STEP.
 SEMR = MASS MATRIX REDUCTION STEP (INCLUDES EIGENVALUE SOLUTION FOR MODES).
 SEKR = STIFFNESS MATRIX REDUCTION STEP.
 SELG = LOAD MATRIX GENERATION STEP.
 SELR = LOAD MATRIX REDUCTION STEP.
 MODES = T (TRUE) IF NORMAL MODES OR BUCKLING MODES CALCULATED.
 DYNRED = T (TRUE) MEANS GENERALIZED DYNAMIC AND/OR COMPONENT MODE REDUCTION
PERFORMED.
 SOLLIN = T (TRUE) IF LINEAR SOLUTION EXISTS IN DATABASE.
 PVALID = P-DISTRIBUTION ID OF P-VALUE FOR P-ELEMENTS
 LOOPID = THE LAST LOOPID VALUE USED IN THE NONLINEAR ANALYSIS.  USEFUL FOR
RESTARTS.
 SOLNL = T (TRUE) IF NONLINEAR SOLUTION EXISTS IN DATABASE.
 DESIGN CYCLE = THE LAST DESIGN CYCLE (ONLY VALID IN OPTIMIZATION).
 SENSITIVITY = SENSITIVITY MATRIX GENERATION FLAG.
1                                         * * * END OF JOB * * *
```