

Schutzvermerk nach DIN ISO 16016 beachten !

Erstellt mit ELCAD/AUCOPLAN (R) 7.6.0 SP2

Alle Leitungen ohne Querschnittsangabe sind H07V/K gy. 1.5 mm²

Erhöhe ab 6000 um 2000
Ergebnis:

\a5000 \A5000	X\a5000 X\A5000
\a5000\A5000	X\a5000X\A5000
\a5000\A5000\a5000	X\a5000X\A5000x\a5000
\a5000 \A5000	X\a5000 X\A5000
\a5000/ \A5000	X\a5000/ \A5000
\a10000 \A10000	X\a10000 X\A10000
\a10000\A10000\a10000	X\a10000\A10000\a10000x
\a10000\A10000	X\a10000X\A10000x
\a10000 \A10000	X\a10000 X\A10000
\a10000/ \A10000	X\a10000/ X\A10000

\a5000 \A10000	X\a5000 X\A5000
\a5000\A5000	X\a5000X\A5000
\a5000\A5000\a5000	X\a5000X\A5000x\a5000
\a5000 \A5000	X\a5000 X\A5000
\a5000/ \A5000	X\a5000/ \A5000
\a12000 \A10000	X\a12000 X\A10000
\a12000\A10000\a12000	X\a12000\A10000\a12000x
\a12000\A10000	X\a12000X\A10000x
\a12000 \A10000	X\a12000 X\A10000
\a12000/ \A10000	X\a12000/ X\A10000

R. Änderung		Datum	Name	Norm	Ursprung	Ersatz für	Ersatz durch	Bandantrieb Stromlaufplan 8	Band Links- und Rechtsverlauf 1	Zeichnungsnummer	=A1.D Bandantrieb 1x	+C1
1		2		3		4		5		7		8
Blatt 8		8		Bl.						DEMO_760		

