

Pos.	Sik.
A-1601 - A-1618	
Material	
Stahlblech 2.5mm	
Oberfläche	
OF9	

A-1603	4	3703	80	80	5	4	886	127
	4	3703	80	80	5	4	886	227
	8							
	1	1641	80	80	5	4	820	120
A-1605	4	3547	80	80	5	4	847	134
	1	3547	80	80	5	4	847	135
	5	3547	80	80	5	4	847	136
	6	3547	80	80	5	4	847	223
	10	3547	80	80	5	4	847	234
	32							
A-1606	1	3287	80	80	5	4	782	133
	1	3287	80	80	5	4	782	233
	2							
A-1607	1	2767	80	80	4	3	869	139
	1	2767	80	80	4	3	869	239
	2							
A-1608	1	2526	80	80	4	3	789	128
	1	2526	80	80	4	3	789	228
	2							
A-1609	1	2492	80	80	4	3	777	131
	1	2492	80	80	4	3	777	231
	2							
A-1610	1	2326	80	80	4	3	722	231
	1	2196	80	80	4	3	679	131
	1	1134	80	80	2	1	974	128
A-1612	1	1134	80	80	2	1	974	228
	2							
	2							
A-1613	1	1077	80	80	2	1	917	128
	1	1077	80	80	2	1	917	228
	2							
A-1614	1	963	80	80	2	1	803	138
	1	963	80	80	2	1	803	238
	2							
A-1615	1	912	80	80	2	1	752	124
	1	912	80	80	2	1	752	224
	2							
A-1616	1	696	80	80	2	1	536	140
	1	696	80	80	2	1	536	240
	2							
A-1617	1	695	80	80	2	1	535	124
	1	695	80	80	2	1	535	224
	2							
A-1618	1	601	80	80	2	1	441	132
	1	601	80	80	2	1	441	232
	2							

